







Date: 08-08-2025

ADVANCE VALVES GLOBAL LLP

PLOT NO 142 A & B, NOIDA SPECIAL ECONOMIC ZONE, PHASE II NOIDA. GAUTAM-BUDH-NAGAR PIN - 201305 ROHIT MODWEL PHONE - +91 120 4796900 EMAIL rohit.modwel@advancevalves.com WEB - www.advancevalves.com

Advance Valves commenced manufacturing Industrial Valves over 25 years ago, in 1986. The Company was promoted and is presently led by Mr. Uma Shanker. Since then Advance Valves has established its position among the top 5 quality manufacturers internationally in its product range. Advance Valves is today considered a pioneer in technology for its Dual Plate Check & Balancing Valves, and even for its Butterfly Valves, especially in the domestic market. Advance Valves has been regularly supplying its products to the Oil and Gas, Refineries and Petrochemical, Power, Water, Fertiliser, Steel, and HVAC sectors. Today, Advance Valves interacts with all the major clients and EPC's both in the domestic markets as well as globally. Advance Valves specializes in the manufacture of Dual Plate Check Valves (as per API 594/API 6D), High Performance Metal Seated and Soft Seated Butterfly Valves (as per API 609) in metallurgies suitable for all petrochemical, sour services, seawater services, power & chemical, mining, power and oxygen sectors, amongst other applications. These include offerings in Aluminum Bronze, Duplex S.S., Titanium, Hastelloy, Alloy 20, Inco Alloy amongst other super alloys. Our Balancing Valves are considered to be a de-facto standard in the Indian HVAC sector.

Products Description









DUAL PLATE CHECK VALVE









Technical Details

The salient features include:- 1. Sizes from 2" to 80" diameter. 2. ANSI Class 125 to ANSI Class 2500. 3. API 6A valves ranging from API 5000 to API 10000. 4. Suitable for -196° C (Cryogenic) to 900° C (Fire Safe applications). 5. Soft and Metal Seated. 7. Fugitive Emission Free Retainerless Design. 8. Models: Wafer, Double & Mono Flanged, Lugged & Sold Lugged, Butt Welded & Hub Ended, Extended Flanged Body, Jacketed Bodies, Ring Type Joints (RTJs) 9. Full Cladding. 10. Zero Velocity Non Slamming Characteristics. 12. No Valve - Induced Water Hammer Effect. Design Features The Dual Plate Check Valve is an all purpose non return valve that is much stronger, lighter in weight and smaller in size compared to a conventional swing check valve or lift check valve. The Dual Plate Check Valve design is the outcome of attempts to solve the problems associated with conventional swing check valve and lift check valve. The Dual Plate Check Valve employs two-spring-loaded plates hinged on a central hinge pin. When the flow decreases, the plates close by the action of torsion spring before flow reversal takes place. This design offers the twin advantages of No Water Hammer and Non Slam simultaneously. All features put together make the Dual Plate Check Valve as the most efficient & versatile design. It is also referred to as SILENT CHECK VALVE Dual Plate Check Valve can be classified as Zero Velocity Valve. The design has everything which the other conventional valves miss. It is a valve most efficient in operation irrespective of fluid and service conditions and the easiest to handle and install in any piping system with no constraints, NO WATER HAMMER To eliminate water hammer, a Check Valve should close before the onset of reverse flow. Water hammer is almost non existent in dual plate check valves since closing of the valve does not depend on back pressure and back flow. Each plate being half the size of a swing check disc provides a straight flow path, offering least resistance. Due to spring assisted closing, valve closure starts as soon as flow velocity reduces below the designed minimum velocity and thereafter the closing rate flows the flow velocity reduction pattern. The valve closes as the flow velocity approaches zero and well before the flow reverses. This eliminates water hammer. In the figure the Heavy Disc in Swing Check Valves develops heavy momentum as it swings to the closed position. NO SLAMMING The Dual Plate Check Valve design is classified as "Non-Slam Design". The disc in a swing check valve is hinged at the top. As the flow reduces, the closure of disc is influenced by force of gravity and high inertia of the heavy disc. This momentum can cause severe damage when the disc slams on to the valve seat. To reduce this, one has to go for a balancing weight/dash pot arrangement etc. This makes the valve more expensive and bulky. Furthermore, any counter weight/dash pot arrangement is counterproductive as far as prevention of water hammer is concerned. The two plates in Dual Plate Check Valve are hinged in the center vertically for horizontal installations, altogether eliminating the effect of the gravity. Also the momentum developed as they move to the closed position is only a fraction of what is developed in a swing check valve as the weight of each plate is 1/4th the weight of swing disc and the tip velocity is less than half. Further due to spring assisted closing, the valve closes as the flow velocity approaches zero and before the flow reversal. As it starts closing, the flow as such cushions the plates and seat, hence minimizing slamming. INDEPENDENT PLATE SUSPENSION For valve sizes 450mm (18") NB and above, each plate is supported independent of each other. In any position (Horizontal or Vertical) each plate's weight is directly transferred to the body. LOWER PRESSURE DROP The design of the Dual Plate Check Valve divides the total force in half, since each plate covers only one half the area of a swing check disc. One half the forces on each plate require one-half thickness, hence onefourth the mass of a swing check disc. Ff (hinge friction) plus Fs (spring force) times 0.75B (force point) minus F (force) times B (width) equals zero for equilibrium. Ff (Friction of Hinge) + Fs (0.75B) - FB = 0 Therefore, F = 0.75 Fs + Ff (Friction of Hinge) B The weight of the plates does not increase the force required to move the plates. Dual Plate Check Valve has much lower pressure drop due to lower force. The best analogy between a swing check valve and Dual plate Check Valve would be a door hinged from the top and a door hinged on its side with an appropriate door closure. The force required for operating the two doors can be just visualized and compared. LOWER WEAR & TEAR OF SEAT FACES The









ITC HS Code 848130 **Certification Category** System Standard Certification/ Standard ISO **BUREAU VERITAS Issuing Agency** Date of Issue Date of Expiry ADVANCE VALVES PVT. LTD. ADVANCE VALVES SOLUTION Certificate Image AND DVANCE VALVES GLOBAL LLP AND VES GLOBAL LLF ٨ Λ Standard ISO 9001:2008 anager VALVES GLOBAL LLP MANUFA DIDA SPECIAL ECONOMIC OF CHE SE - II, NOIDA - 201 305, AN ISO 9001:2008 VELOPMENT, MANUFACTURING, SUPF CHECK VALVES, BUTTERFLY VALVES INCING VALVES FOR SITES 1,2,3 & 4, S NAS 3

> Off-Floor, Frishania' Marvish M Nor Edite, Off Sair Viter Road

End Use Sectors

Product Images

Oil & Gas, Power, Steel & Mining, LNG & Cryogenic, Marine & Water, Chemical &

Marwah Centre' Bh-Floor, Krishanla/Marwah Marg, Opp, Ansa Industrial Edites, Off Salv Viter Road, Andren (East), Mumbar - 400 072, Veta.

















BUTTERFLY TRIPLE OFFSET VALVE









Technical Details	The salient features include :- • 3" to 120" • High pressure range of ANSI # 300, # 600 & #900 • Suitable for -196° C (Cryogenic) to 900° C (Fire Safe applications) • Bi-directional performance • End connections to suit, including Wafer, Lugged, Flanged, Butt Weld, Special design include Jacketed, Zero leakage & bi directional • Metal to Metal seated, thus intrinsically fire safe • Standard compliance with API 609, 598, 607, BS 6364 amongst others 1. Design Features 2. Construction Features 3. Installation Dimensions Design Features Advance Valves metal seating high pressure butterfly valves provides a bi-directional bubble tight shut off. This is achieved by introducing state-of-the-art triple eccentric disc geometry. The valve shaft is off-set against the seal, (1st off-set), and against center line of the valve (2ndt off-set). The seating edges are machined with a continuously changing slope from an angle alpha on top of the oval seat ring to an angle beta at the opposite side (3rd off-set angular). This geometry ensures that the seat ring stays clear of the seat except at the final shut-off position, resulting in long seat life and operating cycles in excess of 500 000. Construction Features The valve seal, is manufactured from laminated stainless steel with PTFE or grap oil laminate depending on the applications. The seal is held in position by a bolt-on retaining ring and, together with the stainless seat ring, is easily replaceable. A gasket prevents leakage around the seal ring. The metal seating valve can operate within a temperature of -249° C to +600° C. Valve designs for cryogenic applications are available on request. For low temperature applications, the metal seat can be substituted by a PTFE seat. Advance High Pressure Butterfly Valves are manufactured in a wide range of materials to suit most applications. For low temperature applications, the metal seat can be substituted by a PTFE seat. Advance High Pressure Butterfly Valves are manufactured in a wide range of materials to suit most applicati
ITC HS Code	848180
Certification Category	Product Standard
Certification/ Standard	API
Issuing Agency	API
Date of Issue	14-12-2015
Date of Expiry	14-09-2017









BRAND INDIA ENGINEERING

	ernal certification www.api.org/certification	
Certificate Image	May 16 2017 Automatic Particle Convertie Zume Automatic Nationales - Editional Liber Particle Regional Convertie Zume Particle Regional Convertie Convert Liber Particle Regional Converties - Editional Convert	Certificate of Authority to use the Official API Monogram License Number: 699-6972 creases
	RE: Certifications 609-0072	The American Petroleum Institute hereity grants to
	APItas selended the explosition dates of your certification(s) to September 14, 2017. You can welly the status of your API certification(s) on the API Composite List by using the following URL: <u>the //composite/status/org/Composite/ListASP2</u> DSI=facility_D=6274	ADVANCE VALVES GLOBAL 142 A & P, Noida Spacial Economic Zone Phase III, Noida
	If you have an APICR ISO 9001 or ISO 14001 Certificate of Registration, this extension does not include those certificates since API's accreditation requirements do not allow the extension of registrations beyond their expiration date.	Gautam Budha Nagar, Uttar Pradesh India
	If you have not yet submitted your renewell documentation, please do so as soon as possible. If you have submitted renewal documentation and your audit has not been scheduled and/or performed, an API auditor will contact you shortly.	the right to use the Official JPI Monogram ⁶ on manufactured products under the conditions in the official publications, of the Amelican Petroleum Institute entities API Spec Q1 and API Standard 609 and in accordance with the provision of the Lonese American.
	If your audit has already been performed, this later does not extend or otherwise change your due date for submiting corrective addres to any proceedimenties. A returnee, any decision on certification resulting from a review of your audit institiates its extension; unless otherwise specified.	American Potroleum artican nute: 6954072
	The extension of your certificates is contingent upon the payment of any outstanding balances. API may withdraw this extension at its discretion for any wrpaids, ownodue balances. Any outstanding balances multible paid in order to avaid supprintion or cancellation of your certifications. APPI will not revealve the audit or composes of bollioss with outstanding balances.	Institute The American Perceloum histoter reserves the right to involve this authorization to use the Official APA Monogram for any reasons satisfactory to the iloard of Directors of the American Perceloum Institute.
	APIsitives to complete messell necetification prior to a cetificatir's explantion. However, just as the demand fix oil and natural gas has instande our the basis toward years, so has the demand for mecogrammed explanmet and API-centifications. While the demand has instande API's possible (inc., API's centification) thereafty is improve there possible (inc., the basis) the term.	Caboy B Sciance: Sector 7.5.4. Customer Property OdS Exclance: Sector 7.5.4. Customer Property
	Sincerely,	Effective Date: DECEMBER 14, 2013 Expiration Date: DECEMBER 14, 2018 Te why the authentity of this tenses, p to remagnizing transposition. Some of some sources town
	à	
	Lisa Salley Vice President, API Global Industry Services	

End Use Sectors

Product Images

Oil & Gas. Power. Steel & Mining. LNG & Cryogenic, Marine & Water, Chemical &













BRAND INDIA ENGINEERING

E-CATALOGUE



BUTTERFLY DOUBLE OFFSET VALVE

Technical Details	Advance Butterfly Valve has, over a period of years, established a reputation for manufacturing high technology valves. Our range of double offset butterfly valves are manufactured in sizes from 80mm to 3000mm and pressure from 10 Bar (class 125) to 20 Bar (class 150). The valves are available in wafer, lugged and double flanged configurations. A wide variety of drilling can be accommodated to meet most European, American and Asian specifications. Our design procedure include finite element stress analysis to ensure material suitability and strength The salient features include:- • 3" to 120" • Upto ANSI # 150 • From – 50° to 205° C • End connections to suit, including Wafer, Lugged, Flanged, Zero leakage & bi directional • EPDM, Buna N, Viton sealing • Standard compliance with 609 & 598 among others Construction Features Advance Valves is the leader in manufacturing of high performance valves, offering a comprehensive range of elastomers, PTFE and metal seating valves. Double Eccentric - Butterfly valves are manufactured in sizes from 3" to 120". It is available in wafer, lug-type and fully flanged configurations. Flange drilling can accommodate BS 4504, DIN 2631/2/3/4 as well as ANSI B 16, 5, API 605 and AWWA C207. Elastomer-seal valves operate on the double off-set principle and are pressure rated up to 25 Bar.
ITC HS Code	848180
Certification Category	Product Standard
Certification/ Standard	POD FROM BHEL, INDIA
Issuing Agency	BHEL
Date of Issue	22-07-2006
Date of Expiry	01-06-2017











End Use Sectors

Certificate Image

Product Images

G & Cryogenic, Marine & Water, Chemical &



<u>...</u>



BUTTERFLY CONCENTRIC VALVE









Technical Details

Advance Butterfly Valve are designed & manufactured to have optimum mix of structural stability, flow efficiency & effective seating coupled with advantage of light weight, compact design and ease of operation. Only a quarter turn is needed to fully open or close the valves. The salient features include:- • Fit n Forget' Butterfly Valve - internally molded liner • 2" to 24" • Upto ANSI # 150 • From - 50° to 205° C • End connection in Wafer, Lugged & Flanged Models • Lining and metallurgy to suit a wide variety of applications, including sea water & water desalination plants • Seal type (EPDM, Buna N, Viton) • Standard compliance with API 609 & 598 Design Features The valves are designed and manufactured to have optimal mix of structural stability, flow efficiency and effective seating coupled with advantage of light weight, compact design and ease of operation. The valves are provided with integrally moulded elastomer body liner for perfect seating and complete isolation of body material from fluid media. No gaskets are required as the body liner effects a perfect seal between the valve body and the mating pipe flanges. The valves are designed using Finite Element Methods. Advance Butterfly Valves conform to BS: 5155, IS: 13095 and also API 609. It also generally complies with AWWA C-504, International standard ISO 10631 and draft European standard pr EN 593. Construction Features Body is one piece design. Top Flange is designed to mount required Valve Operator. Body Liner is integrally moulded and bonded to the body. It provides the seating to valve disc, primary seal to the stem and 'gasket' joint with mating pipe flanges. Integrally moulded liner resists any stretching or distortion of the liner which is a common problem of loosely fitted liner leading to frequent replacements. Valve Disc material covers wide range of applications. It is optimally designed to have an ideal combination of strength and flow efficiency. Stem For optimal combination of flow efficiency and structural stability, Valves upto 200mm (8") have two piece stem. For sizes 250mm (10") to 600mm (24") N.B. stem is in single piece construction which ensures better distribution of weight of the disc. The stem drives the disc through taper pin(s) to eliminate any backlash between Stem & Disc. The material of construction for stem has been standardised as High Tensile Stainless steel (AISI 410). Stem Seal Arrangement Primary Sealing is provided by preloaded contact between flat seat surface and rounded polished disc hub area. Secondary Sealing is provided by the interference fit between stem and stem hole in seat at all positions. Even a tertiary sealing has been provided by fitting moulded O-ring between stem and bush supported by atmospheric sealing with O-rings. Thus Advance Butterfly Valves provide perfect sealing needing no other gland packing End Connections Wafer type flanges are as per BS 4504 PN 10 & 16, BS 1560 classes 125 & 150, ANSI B 16.5 Class 150, ANSI B 16.1 Class 125, BS 10 Table D, E & F and Indian Standard IS 6392 Table 10 to 20. Lug type valves are supplied to suit customer's specifications. Facilities Technology Advantages Rubber technology is fully developed in-house with facilities to mould, process all elastomers including mixing, vulcanizing and metal to elastomers bonding. The integral liner concept is a fail-safe design. Tests Offered Extensive in-house testing facilities are available to fully ensure quality at all stages. These include: • Elastomer Test for Tension, Compression set, Hardness, Specific Gravity, Adhesion & Abrasion Resistance. • Dye Penetrant Test • Tests of Actuators (both electric & pneumatic type) • Hydrostatic Pressure Testing for shell & seat • Pneumatic Testing for seat • Valve operating torque test. Facilities for Pressure Drop test and Life cycle test exist for valid for upto 500 mm (20") NB. Apart from above, other NDT processes including MPI & Ultrasonic Test and tests for chemical & physical properties including special tests e.g. low temperature impact Test, Inter-granular Corrosion Test etc. are also offered to meet customer's requirement through independent Approved Inspection and Test Laboratories. Valve Testing: (Hydrostatic) Each valve is hydrostatically tested for seat & shell tests as per applicable standards. Additional tests as required can be carried out as per customer's specification and requirement.









ITC HS Code	848180	
Certification Category	Product Standard	
Certification/ Standard	UL	
Issuing Agency	UL	
Date of Issue	Castilizate of Compliance	Certificate of Compliance
Date of Expiry	Certion North 2010/26-24/26/2010 Certion North 2010/26-24/26/2010 Extratils.2019.24/2020 Extratils.	Other Other Other Page 1 of 2 Standing
Certificate Image	Laboratories Inc.	Laboratories Inc
	<text><text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text></text>	<text><footnote><footnote><section-header></section-header></footnote></footnote></text>

Certification Category	System Standard
Certification/ Standard	CE
Issuing Agency	BUREAU VERITAS
Date of Issue	17-08-2016
Date of Expiry	01-04-2019









BRAND INDIA ENGINEERING



End Use Sectors

Oil & Gas, Power, Steel & Mining, LNG & Cryogenic, Marine & Water, Chemical &



Certificate Image

Product Images













Sectors of Interest	Oil & Gas, Power, Steel & Mining, LNG & Cryogenic, Marine & Water, Chemical & Fertilizer, HVAC
Is OEM Supplier?	Indigenous
Is After Sales Service Provider?	No
Importance of niche products	DUAL PLATE CHECK VALVE • Metal to metal, Soft seating (resilient seals) & Dual Seating • Fugitive emission free design, • Completely Rubber Lined & Exotic Cladded Valves available; • Cryogenic to Fire Safe Applications; • Independent Plate Suspension; • Wide Selection of Metallurgy. BUTTERFLY TRIPLE OFFSET VALVE • Three offsets give tight sealing in a metal to metal configuration • Fire safe metal to metal seated – API 607 certified • Fugitive Emission free certified as per ISO 15848 from –196 deg C to +450 deg C • Zero Leakage, Low Emission; • One Piece Stem.
Potential market of niche products	Oil & Gas, Power, Steel & Mining, LNG & Cryogenic, Marine & Water, Chemical & Fertilizer, HVAC
Product Supply Record	1. RAPID- MALAYSIA 2. UMM LULU-UAE 3. BAB HABSHAN-UAE 4. BAB COMPRESSION-UAE 5. AGFA-UAE
Patented Technologies	1. Patent of Manual Balancing Valve (Patent Registration No- US 9512925 B2, Dec 6th, 2006)
Awards/Accolades	1. FLUOR APPRECIATION AWARD 2. CERTIFICATE OF EXCELLENCE From IES 3. HVAC & R EXCELLENCE AWARD From Bry-Ali. 4. Udyog Ratna Award 5. IFSY AWARD 6. VENTCONF AWARD 7. API MEET APPRECIATION AWARD 8. APPRECIATION AWARD FROM SKEC 9. RACON APPRECIATION AWARD 10. We do have so many Approvals from different End Users all over the globe.